


Chapter 7: Tailwind CSS with React

7.1 Introduction to Tailwind CSS

7.1.1 What is Tailwind CSS?

- * Tailwind CSS is a **utility-first** CSS framework for rapidly building custom user interfaces.
- * Instead of writing custom CSS, we use **pre-defined utility** classes to style elements directly in our HTML or JSX.
- * It is **highly customizable, responsive** and modern.
- * Tailwind CSS works **seamlessly with React** and helps in building beautiful UIs faster.



Key Points:

- ✓ Tailwind CSS is a utility-first CSS framework.
- ✓ It contains small utility classes to build any design.
- ✓ It is fast, flexible and highly customizable.
- ✓ It reduces the need to write custom CSS.



7.1.2 Why Use Tailwind CSS?

- * **Speeds up development** by using ready-made utility classes.
- * Ensures **consistent design** across the project.
- * **Fully responsive** - breakpoints are built-in.
- * Easy **customization** through `tailwind.config.js`.
- * **Smaller CSS file size** in production (due to purging unused styles).



7.1.3 How Tailwind CSS Works?

Add Tailwind
to Project

Configure
Tailwind

Use Utility
Classes in JSX

Build & Get
Optimized CSS



Example:

Instead of writing custom CSS:

```
.btn { background: blue; color: white; padding: 10px; }
```

In Tailwind CSS:

```
<button class="bg-blue-500 text-white px-4 py-2 rounded">Click Me</button>
```



Key Takeaway:

-  Tailwind CSS helps us build **modern, responsive** and beautiful UIs in React applications **quickly** using utility classes.



7.2 Installation

7.2.1 Prerequisites

- * Basic knowledge of **React** and **Node.js**.
- * Make sure you have **Node.js** and **npm** installed.



7.2.2 Steps to Install Tailwind CSS in React

Follow the steps below to install and set up Tailwind CSS in your React project.

Step 1 Create a new **React project** (if you don't have one).

```
npx create-react-app my-app  
cd my-app
```



Step 2 Install **Tailwind CSS** and its dependencies.

```
npm install -D tailwindcss postcss autoprefixer
```



Step 3 Initialize Tailwind CSS.

```
npx tailwindcss init -p
```



Step 4 Configure the content paths in **tailwind.config.js**.

```
/** @type {import('tailwindcss').Config} */  
module.exports = {  
  content: ["/src/**/*.{js,jsx,ts,tsx}"],  
  theme: { extend: {} },  
  plugins: [],  
}
```



Step 5 Add **Tailwind directives** to your CSS file.
(src/index.css)

```
@tailwind base;  
@tailwind components;  
@tailwind utilities;
```



Step 6 Start your **development server**.

```
npm start
```



Key Points :

- ✓ Tailwind CSS is installed as a dev dependency.
- ✓ The **-p** flag creates both **tailwind.config.js** and **postcss.config.js**.
- ✓ Configure the correct content paths for Tailwind to scan your files.
- ✓ Always import Tailwind directives in your main CSS file.



Key Takeaway :



With just a few **simple steps**, Tailwind CSS is ready to use in your **React** project!

7.3 Utility Classes

7.3.1 What are Utility Classes?

- * Tailwind CSS provides **low-level utility classes** that let you build custom designs without writing custom CSS.
- * Each class does **one single thing**.
- * By **combining** these classes, we can create complex layouts and beautiful designs.

```
<div class="
  p-4 bg-blue-500
  text-white
  rounded-md">
...</div>
```

7.3.2 Common Categories of Utility Classes

Category		Purpose	Examples
	Spacing	For margin, padding, gap, etc.	m-4, mt-2, p-6, px-4, gap-4
	Colors	For background, text, border colors.	bg-blue-500, text-white, border-gray-300
	Typography	For font size, weight, family, etc.	text-lg, font-bold, font-sans, leading-relaxed
	Layout	For display, position, width, height, etc.	block, flex, grid, w-full, h-64, hidden
	Flexbox & Grid	For alignment and distribution.	flex, justify-center, items-center, grid, grid-cols-3
	Borders	For border width, style, radius, etc.	border, border-2, border-dashed, rounded-lg
	Effects	For shadow, opacity, blur, etc.	shadow-md, opacity-75, blur-sm
	Interactivity	For hover, focus, active states.	hover:bg-blue-600, focus:outline-none, active:scale-95

7.3.3 Examples of Utility Classes

`<button class="bg-blue-500 text-white px-4 py-2 rounded-md">` → Blue background, white text, Click Me
`</button>`
horizontal & vertical padding, rounded corners.

`<div class="p-6 m-4 border border-gray-300 rounded-lg">` → Padding 24px, margin 16px, Content
`</div>`
gray border, large rounded corners.

`<h1 class="text-2xl font-bold text-center text-indigo-600">` → Large text, bold font, center
Hello Tailwind CSS!
`</h1>`
aligned, indigo color.



Key Points :

- ✓ Utility classes are the building blocks of Tailwind CSS.
- ✓ They help in creating consistent, responsive and modern designs.
- ✓ No need to write custom CSS for most of the styling.



Key Takeaway :




Mastering **utility classes** is the key to building **beautiful** user interfaces quickly with Tailwind CSS.



7.4 Responsive Classes


7.4.1 What are Responsive Classes?

- * Responsive classes allow you to apply different styles based on the **screen size**.
- * Tailwind uses a **mobile-first** approach.
- * You can add **prefixes** before utility classes to apply styles at specific breakpoints.



7.4.2 Breakpoints in Tailwind CSS

Prefix	Min Width	Devices	Example
sm	640px	Small devices (landscape phones)	sm:text-lg
md	768px	Medium devices (tablets)	md:p-6
lg	1024px	Large devices (laptops)	lg:grid-cols-2
xl	1280px	Extra large devices (desktops)	xl:text-2xl
2xl	1536px	Extra extra large devices	2xl:w-1/2




Text size increases as screen size increases.

7.4.3 How Responsive Classes Work?

- * Without a prefix → styles apply to **all screen sizes** (default).
- * With a prefix → styles apply from **that breakpoint and above**.
- * Larger screens **inherit** styles from smaller breakpoints unless overridden.

7.4.4 Examples

- `<div class="p-4 sm:p-6 md:p-8 lg:p-10">`
Content
`</div>` → Padding: 16px (default), 24px on sm, 32px on md, 40px on lg and above.
- `<h1 class="text-base sm:text-lg md:text-xl lg:text-2xl xl:text-3xl">` → Text size increases with screen size.
Responsive Heading
`</h1>`
- `<div class="grid grid-cols-1 md:grid-cols-2 lg:grid-cols-3">` → 1 column by default, 2 columns on md, 3 columns on lg and above.
...
`</div>`
- `` → Image width changes at different breakpoints.



Key Points :

- ✓ Tailwind CSS is **mobile-first**.
- ✓ Use prefixes (**sm, md, lg, xl, 2xl**) to apply styles at specific breakpoints.
- ✓ Styles added for larger breakpoints **override** smaller ones.
- ✓ This helps in building **fully responsive designs** easily.



Key Takeaway :




Responsive classes in Tailwind CSS make it easy to create layouts and components that look great on **all devices**.



7.5 Flexbox with Tailwind

7.5.1 What is Flexbox?

- Flexbox is a **one-dimensional** layout model in CSS.
- It helps in **arranging items** in a **row** or **column** and aligning them easily.
- Tailwind CSS provides **utility classes** to use Flexbox without writing custom CSS.




7.5.2 Important Flexbox Utility Classes

Category	Classes	Purpose	Example
↔	Container flex	Makes the container a flex container.	<code><div class="flex"> ... </div></code>
■ = ■ =	Direction flex-row flex-col	Sets the direction of flex items.	<code><div class="flex flex-row"> ... </div></code> <code><div class="flex flex-col"> ... </div></code>
	Justify Content justify-start justify-center justify-between justify-end	Aligns items along the main axis (horizontal).	<code><div class="flex justify-center"> ... </div></code>
↑ ↓	Align Items items-start items-center items-end items-stretch	Aligns items along the cross axis (vertical).	<code><div class="flex items-center"> ... </div></code>
≡	Align Content content-start content-center content-between content-end	Aligns multiple lines along the cross axis.	<code><div class="flex flex-wrap content-between"> ... </div></code>
☐☐☐	Wrap flex-wrap flex-nowrap flex-wrap-reverse	Controls wrapping of items.	<code><div class="flex flex-wrap"> ... </div></code>
☐ →	Gap gap-x-*, gap-y-*, gap-*	Adds space between items.	<code><div class="flex gap-4"> ... </div></code>

7.5.3 Examples

1. Center items horizontally and vertically



```
<div class="flex items-center justify-center h-32 bg-gray-100">
  <div class="bg-blue-500 text-white px-4 py-2 rounded">Item</div>
</div>
```

→ Items are centered both horizontally and vertically.



2. Space between items




```
<div class="flex justify-between p-4 bg-gray-100">
  <div class="bg-green-500 w-10 h-10"></div>
  <div class="bg-green-500 w-10 h-10"></div>
  <div class="bg-green-500 w-10 h-10"></div>
</div>
```

→ Items are placed with equal space between them.



3. Column layout with gap



```
<div class="flex flex-col gap-3 p-4 bg-gray-100">
  <div class="bg-purple-500 h-8"></div>
  <div class="bg-purple-500 h-8"></div>
  <div class="bg-purple-500 h-8"></div>
</div>
```

→ Items are arranged in a column with gap between them.



Key Points :

- ✓ Use **flex** to create a flex container.
- ✓ Control direction, alignment, spacing and wrapping using utility classes.
- ✓ Flexbox makes it easy to build modern and responsive layouts.



Key Takeaway :


- 💡 Tailwind CSS Flexbox utilities help in building **powerful layouts** easily without writing custom CSS.



7.6 Grid with Tailwind

7.6.1 What is Grid?

- * CSS Grid is a **two-dimensional** layout system.
- * It helps in creating **complex layouts** with rows and columns.
- * Tailwind CSS provides **utility classes** to use Grid easily.




7.6.2 Important Grid Utility Classes

Category	Classes	Purpose	Example
	Container grid	Defines a grid container.	<code><div class="grid"> ... </div></code>
	Columns grid-cols-{n} grid-cols-{n1,n2,...}	Defines the number of columns.	<code><div class="grid grid-cols-3"> ... </div></code> <code><div class="grid grid-cols-2 md:grid-cols-4"> ... </div></code>
	Rows grid-rows-{n} grid-rows-{n1,n2,...}	Defines the number of rows.	<code><div class="grid grid-rows-2"> ... </div></code>
	Gap gap-{size} gap-x-{size} gap-y-{size}	Adds gap between grid items.	<code><div class="grid grid-cols-3 gap-4"> ... </div></code> <code><div class="grid grid-cols-3 gap-x-6"> ... </div></code> <code><div class="grid grid-cols-3 gap-y-6"> ... </div></code>
	Column Span col-span-{n}	Makes an item span across columns.	<code><div class="col-span-2"> ... </div></code>
	Row Span row-span-{n}	Makes an item span across rows.	<code><div class="row-span-2"> ... </div></code>
	Justify Items justify-items-start justify-items-center justify-items-end justify-items-stretch	Aligns items horizontally within their cells.	<code><div class="grid justify-items-center"> ... </div></code>
	Align Items items-start items-center items-end items-stretch	Aligns items vertically within their cells.	<code><div class="grid items-center"> ... </div></code>

7.6.3 Examples

1. Simple 3 Column Grid




```
<div class="grid grid-cols-3 gap-4">
  <div class="bg-blue-200 p-4">1</div>
  <div class="bg-blue-200 p-4">2</div>
  <div class="bg-blue-200 p-4">3</div>
</div>
```

→ Creates a grid with 3 equal columns and gap between items.



2. Responsive Grid




```
<div class="grid grid-cols-2 md:grid-cols-3 lg:grid-cols-4 gap-4">
  <div class="bg-green-200 p-3">1</div>
  <div class="bg-green-200 p-3">2</div>
  <div class="bg-green-200 p-3">3</div>
  <div class="bg-green-200 p-3">4</div>
  <div class="bg-green-200 p-3">5</div>
  <div class="bg-green-200 p-3">6</div>
</div>
```

→ 2 columns on small screens, 3 on medium, 4 on large screens.




3. Column & Row Span



```
<div class="grid grid-cols-3 grid-rows-2 gap-4">
  <div class="bg-pink-200 col-span-2">1</div>
  <div class="bg-yellow-200">2</div>
  <div class="bg-green-200">3</div>
  <div class="bg-purple-200">4</div>
</div>
```

→ Item 1 spans across 2 columns. Items are arranged in 2 rows.



Key Points :

- ✓ Use **grid** to create a Grid container.
- ✓ Define the number of columns/rows using utility classes.
- ✓ Use **gap** classes to add space between items.
- ✓ Use **col-span** and **row-span** to make items span multiple cells.
- ✓ Combine Grid with responsive prefixes for better layouts.



Key Takeaway :





Tailwind CSS Grid utilities make it easy to build **powerful, structured** and **responsive** layouts with less code.



7.7 Typography

7.7.1 What is Typography?

- * Typography is the **art of styling text**.
- * Tailwind CSS provides **utility classes** to control the appearance of text easily.
- * It helps in creating **readable** and **beautiful** user interfaces.



7.7.2 Important Typography Utility Classes

Category	Classes	Purpose	Example
T Font Size	text-xs, text-sm, text-base, text-lg, text-xl, text-2xl, text-3xl, text-4xl, text-5xl, text-6xl, text-7xl	Controls the size of the text.	<code><p class="text-3xl">Large Text</p></code>
B Font Weight	font-thin, font-extralight, font-light, font-normal, font-medium, font-semibold, font-bold, font-extrabold, font-black	Controls the thickness or boldness of text.	<code><p class="font-bold">Bold Text</p></code>
I Font Style	italic, not-italic	Makes text italic or not.	<code><p class="italic">Italic Text</p></code>
Aa Text Alignment	text-left, text-center, text-right, text-justify	Aligns the text horizontally.	<code><p class="text-center">Centered Text</p></code>
A Text Color	text-{color} (e.g., text-red-500, text-blue-600, text-gray-700)	Sets the color of the text.	<code><p class="text-blue-600">Blue Text</p></code>
≡ Line Height	leading-none, leading-tight, leading-snug, leading-normal, leading-relaxed, leading-loose	Controls the space between lines.	<code><p class="leading-relaxed">This is text with relaxed line height.</p></code>
Ag Text Decoration	underline, line-through, no-underline	Adds or removes decorations.	<code><p class="underline">Underlined</p></code>
Abc Text Transform	uppercase, lowercase, capitalize, normal-case	Transforms the text case.	<code><p class="uppercase">uppercase text</p></code>
AV Letter Spacing	tracking-tighter, tracking-tight, tracking-normal, tracking-wide, tracking-wider, tracking-widest	Controls the space between letters.	<code><p class="tracking-wide">Wide Letter Spacing</p></code>

7.7.3 Examples

`<h1 class="text-4xl font-extrabold text-indigo-600">Hello Tailwind!</h1>`

→ **Hello Tailwind!** Large, bold and indigo colored text.



`<p class="text-lg text-gray-700 leading-relaxed">Tailwind CSS makes typography simple and effective.</p>`

→ Tailwind CSS makes typography simple and effective. Gray text with relaxed line height.



`<p class="text-center text-green-600 font-semibold">Center aligned and green text.</p>`

→ **Center aligned and green text.** Centered, green and semi-bold text.



`<p class="underline decoration-red-500 uppercase tracking-widest">Tailwind Typography</p>`

→ **TAILWIND TYPOGRAPHY** Uppercase, underlined with wide letter spacing.



Key Points :

- ✓ Tailwind CSS provides powerful utility classes for styling text.
- ✓ You can control font size, weight, style, alignment, color and more easily.
- ✓ Good typography improves readability and user experience.
- ✓ Use responsive prefixes (sm:, md:, lg:, xl.) to adjust typography on different screens.



Key Takeaway :

- With Tailwind CSS typography utilities, you can create **clean, modern** and **visually appealing** text in your applications with minimal effort.



7.8 Colors

7.8.1 What is Colors?






- * Colors are used to make user interfaces **attractive** and **easy to understand**.
- * Tailwind CSS provides a **complete color palette** with multiple shades.
- * We can apply colors to **background**, **text**, **border** and more using utility classes.



Add colors
to your ideas.
Make it
beautiful!



7.8.2 Tailwind CSS Default Color Palette

Category	Shades (Examples)	Usage Example	Preview
Gray	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-gray-500</code> <code>text-gray-700</code> <code>border-gray-300</code>	
Red	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-red-500</code> <code>text-red-600</code> <code>border-red-300</code>	
Blue	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-blue-500</code> <code>text-blue-600</code> <code>border-blue-300</code>	
Green	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-green-500</code> <code>text-green-600</code> <code>border-green-300</code>	
Yellow	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-yellow-400</code> <code>text-yellow-600</code> <code>border-yellow-300</code>	
Indigo	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-indigo-500</code> <code>text-indigo-600</code> <code>border-indigo-300</code>	
Purple	50, 100, 200, 300, 400, 500, 600, 700, 800, 900	<code>bg-purple-500</code> <code>text-purple-600</code> <code>border-purple-300</code>	

7.8.3 Using Colors in Tailwind CSS

- * `bg-{color}-{shade}` - for background color
- * `text-{color}-{shade}` - for text color
- * `border-{color}-{shade}` - for border color
- * `ring-{color}-{shade}` - for ring color
- * `divide-{color}-{shade}` - for dividers

Example Color Usage

<code>bg-blue-500</code>	Background Blue
<code>text-green-600</code>	Text Green
<code>border-red-400</code>	Border Red
<code>ring-purple-500</code>	Ring Purple

7.8.4 Examples

<code><div class="bg-blue-500 text-white p-4 rounded-md"></code> Blue Background <code></div></code>	→	Blue Background White text on blue background.
<code><p class="text-green-600 text-lg font-semibold"></code> Green Text Example <code></p></code>	→	Green Text Example Large green text. Semi-bold font.
<code><div class="border-2 border-red-400 p-4 rounded"></code> Red Border <code></div></code>	→	Red Border Red border around the box.
<code><button class="bg-purple-600 hover:bg-purple-700 text-white px-4 py-2 rounded-lg"></code> Purple Button <code></button></code>	→	Purple Button Purple button with hover effect.

Key Points :

- ✓ Tailwind CSS provides a beautiful and complete color palette.
- ✓ We can use colors for background, text, border, ring and more.
- ✓ Choose proper colors to improve readability and user experience.
- ✓ Use hover and focus colors for interactive elements.



Key Takeaway :



Colors make your UI **attractive** and **user-friendly**.
Tailwind CSS color utilities help you style **beautifully** with minimal effort.




7.9 Spacing

7.9.1 What is Spacing?

- * Spacing is used to control the space **around** and **inside** elements.
- * Tailwind CSS provides utility classes for **margin**, **padding**, **gap** and **space** between elements.
- * It helps in creating **clean**, **balanced** and well-structured layouts.

Spacing Around an Element



7.9.2 Spacing Scale in Tailwind CSS

Class	Spacing (rem)	Pixels (approx)	Class	Spacing (rem)	Pixels (approx)	Notes
0	0rem	0px	5	1.25rem	20px	Use these values with m-* , p-* , gap-* , space-x-* , space-y-* classes. Example: p-4 → 1rem (16px) padding m-2 → 0.5rem (8px) margin
0.5	0.125rem	2px	6	1.5rem	24px	
1	0.25rem	4px	8	2rem	32px	
1.5	0.375rem	6px	10	2.5rem	40px	
2	0.5rem	8px	12	3rem	48px	
2.5	0.625rem	10px	16	4rem	64px	
3	0.75rem	12px	20	5rem	80px	
4	1rem	16px	24	6rem	96px	

7.9.3 Spacing Utility Classes

- * **m-{value}** - margin on all sides
- * **mx-{value}** - margin on left & right
- * **my-{value}** - margin on top & bottom
- * **mt-{value}** - margin on top
- * **mr-{value}** - margin on right
- * **mb-{value}** - margin on bottom
- * **ml-{value}** - margin on left

- * **p-{value}** - padding on all sides
- * **px-{value}** - padding on left & right
- * **py-{value}** - padding on top & bottom
- * **pt-{value}** - padding on top
- * **pr-{value}** - padding on right
- * **pb-{value}** - padding on bottom
- * **pl-{value}** - padding on left

gap-{value} - gap between rows & columns (grid, flex)


space-x-{value} - space between items in x-direction (horizontal)

space-y-{value} - space between items in y-direction (vertical)

7.9.4 Examples


1. Margin Example

```
<div class="m-4 bg-blue-200">  
  Margin 4 (1rem = 16px)  
</div>
```




2. Padding Example

```
<div class="p-6 bg-green-200">  
  Padding 6 (1.5rem = 24px)  
</div>
```




3. Gap in Grid

```
<div class="grid grid-cols-3 gap-4">  
  <div class="bg-yellow-200">1</div>  
  <div class="bg-yellow-200">2</div>  
  <div class="bg-yellow-200">3</div>  
</div>
```




4. Space Between Items (Flex)

```
<div class="flex space-x-4 bg-gray-100 p-2">  
  <div class="bg-pink-300 px-3 py-1">A</div>  
  <div class="bg-pink-300 px-3 py-1">B</div>  
  <div class="bg-pink-300 px-3 py-1">C</div>  
</div>
```



5. Space Between Items (Vertical)

```
<div class="flex flex-col space-y-3 bg-gray-100 p-2">  
  <div class="bg-indigo-300 p-2">Item 1</div>  
  <div class="bg-indigo-300 p-2">Item 2</div>  
  <div class="bg-indigo-300 p-2">Item 3</div>  
</div>
```



Key Points :

- ✓ Use margin (m-*) to control space outside elements.
- ✓ Use padding (p-*) to control space inside elements.
- ✓ Use gap-*, space-x-*, space-y-* to control space between items.
- ✓ Tailwind's spacing scale makes it easy to maintain consistency.



Key Takeaway :



Tailwind CSS spacing utilities help you build **clean**, **consistent** and **well-balanced** layouts with less custom CSS.




7.10 Borders

7.10.1 What are Borders?

- * Borders are used to add an outline or edge around an element.
- * Tailwind CSS provides utility classes to control **border width, style, color** and **radius** easily.
- * We can apply borders to all sides or specific sides of an element.

Example



7.10.2 Border Utility Classes

Category	Classes	Description	Example Class	Preview
Border Width	<code>border</code>	Adds a 1px border	<code><div class="border"></div></code>	
	<code>border-0</code>	No border	<code><div class="border-0"></div></code>	
	<code>border-2</code>	2px border	<code><div class="border-2"></div></code>	
	<code>border-4</code>	4px border	<code><div class="border-4"></div></code>	
	<code>border-8</code>	8px border	<code><div class="border-8"></div></code>	
Border Style	<code>border-solid</code>	Solid border	<code><div class="border border-solid"></div></code>	
	<code>border-dashed</code>	Dashed border	<code><div class="border border-dashed"></div></code>	
	<code>border-dotted</code>	Dotted border	<code><div class="border border-dotted"></div></code>	
	<code>border-double</code>	Double border	<code><div class="border border-double"></div></code>	
	<code>border-none</code>	No border	<code><div class="border border-none"></div></code>	
Border Color	<code>border-gray-300</code>	Gray border	<code><div class="border border-gray-300"></div></code>	
	<code>border-red-500</code>	Red border	<code><div class="border border-red-500"></div></code>	
	<code>border-green-500</code>	Green border	<code><div class="border border-green-500"></div></code>	
	<code>border-blue-500</code>	Blue border	<code><div class="border border-blue-500"></div></code>	
	<code>border-purple-500</code>	Purple border	<code><div class="border border-purple-500"></div></code>	
Border Radius	<code>rounded-none</code>	No radius	<code><div class="border rounded-none"></div></code>	
	<code>rounded-sm</code>	Small radius	<code><div class="border rounded-sm"></div></code>	
	<code>rounded-md</code>	Medium radius	<code><div class="border rounded-md"></div></code>	
	<code>rounded-lg</code>	Large radius	<code><div class="border rounded-lg"></div></code>	
	<code>rounded-xl</code>	Extra large radius	<code><div class="border rounded-xl"></div></code>	
	<code>rounded-2xl</code>	2x extra large radius	<code><div class="border rounded-2xl"></div></code>	
Side Borders	<code>rounded-full</code>	Fully rounded (circle)	<code><div class="border rounded-full"></div></code>	
	<code>border-t</code>	Top border	<code><div class="border-t border-gray-400"></div></code>	
	<code>border-r</code>	Right border	<code><div class="border-r border-gray-400"></div></code>	
	<code>border-b</code>	Bottom border	<code><div class="border-b border-gray-400"></div></code>	
	<code>border-l</code>	Left border	<code><div class="border-l border-gray-400"></div></code>	
	<code>border-x</code>	Left & Right border	<code><div class="border-x border-gray-400"></div></code>	
	<code>border-y</code>	Top & Bottom border	<code><div class="border-y border-gray-400"></div></code>	

7.10.3 Examples

<code><div class="border border-blue-500 p-4 rounded-md"> I have blue border </div></code>	→	I have blue border
<code><div class="border-2 border-dashed border-green-500 p-4 rounded-lg"> Dashed green border </div></code>	→	Dashed green border
<code><div class="border-4 border-double border-red-500 p-4 rounded-xl"> Double red border </div></code>	→	Double red border
<code><div class="border-t-4 border-purple-500 p-4"> Top purple border </div></code>	→	Top purple border
<code><div class="border border-gray-300 rounded-full px-6 py-2"> Fully rounded </div></code>	→	Fully rounded

7.10.4 Notes

- * Default border width is 1px when you use "border" class.
- * Use `border-0` or `border-none` to remove border.
- * Combine border width, style and color classes.
- * Use `rounded-*` classes to control corner radius.
- * Use `border-x` or `border-y` to add borders only on horizontal or vertical sides.

Quick Tip

Borders help in separating content and improving the visual structure of your UI.

Key Points :

- ✓ Use borders to add outlines to elements.
- ✓ Control width, style, color and radius using utility classes.
- ✓ Apply borders to all sides or specific sides as needed.
- ✓ Borders improve the readability and design of your UI.

Key Takeaway :



Tailwind CSS border utilities give you **complete control** over the appearance of borders with minimal and clean code.



Side Border Example					
<code>border-t</code>	<code>border-r</code>	<code>border-b</code>	<code>border-l</code>	<code>border-x</code>	<code>border-y</code>




7.11 Shadows

7.11.1 What are Shadows?

- Shadows are used to create **depth** and **lift** elements above the background.
- Tailwind CSS provides utility classes to easily add **box-shadows** to elements.
- We can control shadow **size**, **darkness** and **position** using different shadow classes.

Example



7.11.2 Shadow Utility Classes

Category	Classes	Description	Example Class	Preview
Basic Shadows	shadow-sm	Small shadow	<code><div class="shadow-sm"></div></code>	
	shadow	Default shadow	<code><div class="shadow"></div></code>	
	shadow-md	Medium shadow	<code><div class="shadow-md"></div></code>	
	shadow-lg	Large shadow	<code><div class="shadow-lg"></div></code>	
	shadow-xl	Extra large shadow	<code><div class="shadow-xl"></div></code>	
	shadow-2xl	Extra extra large shadow	<code><div class="shadow-2xl"></div></code>	
Inner Shadow	shadow-inner	Adds shadow inside the element	<code><div class="shadow-inner"></div></code>	
No Shadow	shadow-none	Removes any existing shadow	<code><div class="shadow-none"></div></code>	
Shadow Color	shadow-gray-400	Adds shadow with custom color	<code><div class="shadow shadow-gray-400"></div></code>	
	shadow-red-500		<code><div class="shadow shadow-red-500"></div></code>	
	shadow-green-500		<code><div class="shadow shadow-green-500"></div></code>	
	shadow-blue-500		<code><div class="shadow shadow-blue-500"></div></code>	
	shadow-purple-500		<code><div class="shadow shadow-purple-500"></div></code>	

7.11.3 Examples

<code><div class="p-4 bg-white shadow-sm rounded-md"> Small Shadow </div></code>	→	Small Shadow
<code><div class="p-4 bg-white shadow rounded-md"> Default Shadow </div></code>	→	Default Shadow
<code><div class="p-4 bg-white shadow-md rounded-md"> Medium Shadow </div></code>	→	Medium Shadow
<code><div class="p-4 bg-white shadow-lg rounded-md"> Large Shadow </div></code>	→	Large Shadow
<code><div class="p-4 bg-white shadow-2xl rounded-md"> Extra Large Shadow </div></code>	→	Extra Large Shadow
<code><div class="p-4 bg-white shadow-inner rounded-md"> Inner Shadow </div></code>	→	Inner Shadow
<code><div class="p-4 bg-white shadow-none border rounded-md"> No Shadow </div></code>	→	No Shadow

7.11.4 Notes

- Default shadows are gray with different sizes and blur.
- Use **shadow-none** to remove shadow.
- Use **shadow-inner** for inner shadow effect.
- Combine with **rounded-*** for better visual appearance.
- Shadows work best on light backgrounds.

Quick Tip

Use shadows to create depth and highlight important elements in your UI.

7.11.5 Custom Shadow (Arbitrary Value)

- You can create custom shadows using square bracket notation.

```
<div class="shadow-[0_10px_15px_rgba(0,0,0,0.25)] p-4 bg-white rounded-md">  
Custom Shadow  
</div>
```

Custom Shadow

How it works?

shadow-[x y blur color]
 x → horizontal offset
 y → vertical offset
 blur → blur radius
 color → shadow color



Key Points :

- Use shadow utility classes to add depth to elements.
- Choose the right shadow size as per the importance of the element.
- Use shadow-none to remove and shadow-inner for inner effects.
- Combine shadows with rounded corners and spacing for beautiful UI.

Key Takeaway :



Tailwind CSS shadow utilities help you create **depth**, **focus** and **hierarchy** in your designs with minimal and consistent code.




7.12 Hover States



7.12.1 What are Hover States?

- * Hover states are used to style an element when the user moves the **mouse** over it.
- * Tailwind CSS provides the **hover:** variant to apply styles on hover.
- * It helps to create **interactive** and **engaging** user interfaces.

Example



7.12.2 Hover Utility Classes

Category	Classes (with hover:)	Description	Example Class	Preview (Hover Effect)
Background Color	<code>hover:bg-blue-500</code> <code>hover:bg-green-500</code> <code>hover:bg-red-500</code> <code>hover:bg-yellow-500</code>	Changes the background color on hover.	<code><button class="bg-blue-500 hover:bg-blue-700 text-white px-4 py-2 rounded">Button</button></code>	Normal → Hover  → 
Text Color	<code>hover:text-blue-600</code> <code>hover:text-green-600</code> <code>hover:text-red-600</code> <code>hover:text-purple-600</code>	Changes the text color on hover.	<code><p class="text-gray-600 hover:text-blue-600">Hover over this text</p></code>	Normal → Hover Hover over this text → Hover over this text
Border Color	<code>hover:border-blue-500</code> <code>hover:border-green-500</code> <code>hover:border-red-500</code>	Changes the border color on hover.	<code><div class="border border-gray-300 hover:border-blue-500 p-4 rounded">Box</div></code>	Normal → Hover  → 
Opacity	<code>hover:opacity-80</code>	Changes the opacity on hover.	<code></code>	Normal → Hover  → 
Scale	<code>hover:scale-105</code>	Enlarges the element slightly on hover.	<code><button class="bg-green-500 text-white px-4 py-2 rounded transform transition hover:scale-105">Click Me</button></code>	Normal → Hover  → 
Shadow	<code>hover:shadow</code> <code>hover:shadow-md</code> <code>hover:shadow-lg</code> <code>hover:shadow-xl</code>	Adds or increases shadow on hover.	<code><div class="p-4 bg-white border rounded hover:shadow-lg transition">Card</div></code>	Normal → Hover  → 
Underline	<code>hover:underline</code>	Adds underline to text on hover.	<code>Learn More</code>	Normal → Hover Learn More → <u>Learn More</u>
Cursor	<code>hover:cursor-pointer</code>	Changes cursor to pointer on hover.	<code><button class="px-4 py-2 bg-purple-500 text-white rounded hover:cursor-pointer">Pointer Button</button></code>	Normal → Hover  → 

7.12.3 Common Usage Examples

```
<button class="bg-blue-500 text-white px-4 py-2 rounded hover:bg-blue-700 transition">Submit</button>
```

→ 

```
<a href="#" class="text-gray-700 hover:text-green-600 font-medium">Home</a>
```

→ 

```
<div class="p-4 border border-gray-300 rounded hover:shadow-lg transition">Hover Over Card</div>
```

→ 

```

```

→ 

```
<button class="px-4 py-2 bg-green-500 text-white rounded hover:bg-green-600 hover:scale-105 transition">Get Started</button>
```

→ 

7.12.4 Notes

- * Use **hover:** followed by any utility class to apply styles on hover.
- * **Transition** utilities (`transition`, `duration-300`, `ease-in-out`) make hover effects smooth.
- * Hover works best on devices with a mouse.
- * You can combine multiple hover utilities for powerful effects.

Tip

Combine **hover:** with **transform** and **transition** for beautiful interactive effects.

Example: `hover:scale-105 hover:shadow-lg`

Key Points :

- ✓ Hover states improve user interaction and experience.
- ✓ Use `hover:utility-class` to style elements on hover.
- ✓ Combine hover utilities with transition for smooth effects.
- ✓ Common hover utilities: `bg`, `text`, `border`, `opacity`, `scale`, `shadow`, `underline`, `cursor`.

Key Takeaway :

Tailwind CSS hover utilities help you create responsive and **interactive UI** with minimal code and maximum impact.




7.13 Transitions

7.13.1 What are Transitions?

- Transitions are used to change CSS properties **smoothly** over a specified duration.
- Tailwind CSS provides transition utilities to apply **transitions** easily.
- They make UI interactions feel **smooth** and **professional**.

Example



7.13.2 Transition Utility Classes

Category	Classes	Description	Example Class	Preview (Effect)
Transition Property	transition-all transition transition-colors transition-opacity transition-shadow transition-transform	Apply transition to all properties. Apply transition to CSS properties. Only opacity. Only shadow. Only transform.	<code><div class="transition-all"></div></code> <code><div class="transition"></div></code> <code><div class="transition-colors"></div></code> <code><div class="transition-opacity"></div></code> <code><div class="transition-shadow"></div></code> <code><div class="transition-transform"></div></code>	Smooth change for all properties Smooth change for property Smooth color change Smooth opacity change Smooth shadow change Smooth transform change
Transition Duration	duration-75 duration-100 duration-150 duration-200 duration-300 duration-500 duration-700 duration-1000	Set how long the transition takes.	<code><div class="duration-75"></div></code> <code><div class="duration-100"></div></code> <code><div class="duration-150"></div></code> <code><div class="duration-200"></div></code> <code><div class="duration-300"></div></code> <code><div class="duration-500"></div></code> <code><div class="duration-700"></div></code> <code><div class="duration-1000"></div></code>	Very fast (75ms) Fast (100ms) Slightly fast (150ms) Default (200ms) Smooth (300ms) Slow (500ms) Slower (700ms) Very slow (1000ms)
Transition Timing Function	ease-linear ease-in ease-out ease-in-out	Control the speed curve of the transition.	<code><div class="ease-linear"></div></code> <code><div class="ease-in"></div></code> <code><div class="ease-out"></div></code> <code><div class="ease-in-out"></div></code>	✓ Constant speed ✓ Slow start ✓ Slow end ✓ Slow start and slow end
Transition Delay	delay-75 delay-100 delay-150 delay-200 delay-300 delay-500 delay-700 delay-1000	Delay before the transition starts.	<code><div class="delay-75"></div></code> <code><div class="delay-100"></div></code> <code><div class="delay-150"></div></code> <code><div class="delay-200"></div></code> <code><div class="delay-300"></div></code> <code><div class="delay-500"></div></code> <code><div class="delay-700"></div></code> <code><div class="delay-1000"></div></code>	Delay 75ms Delay 100ms Delay 150ms Delay 200ms Delay 300ms Delay 500ms Delay 700ms Delay 1000ms
Combine Transition Utilities	transition-all duration-300 ease-in-out delay-100	Combine all utilities to create smooth and delayed effects.	<code><button class="transition-all duration-300 ease-in-out delay-100 bg-blue-500 hover:bg-blue-700 text-white px-4 py-2 rounded">Button</button></code>	Normal → Hover

7.13.3 Examples

```
<button class="bg-green-500 text-white px-4 py-2 rounded transition-all duration-300 hover:bg-green-700">Save</button>
```



```
<button class="bg-purple-500 text-white px-4 py-2 rounded transition-transform duration-300 hover:scale-110">Zoom</button>
```



```
<div class="p-6 bg-white shadow-md transition-shadow duration-300 hover:shadow-xl rounded-lg">Card</div>
```



```
<a href="#" class="text-blue-600 underline transition-colors duration-200 hover:text-blue-800">Learn More</a>
```



```
<button class="bg-red-500 text-white px-4 py-2 rounded transition-opacity duration-500 hover:opacity-50">Fade</button>
```



7.13.4 Notes

- Use **transition-all** for all properties.
- Use **transition-colors** for color changes only.
- Default duration is **150ms** (**duration-150**).
- Use **ease-in-out** for smooth natural animation.
- Add **delay** if you want the transition to start after some time.

Quick Tip

Always combine transition with duration and ease for the best results!



How it works?

- transition-property** → What to animate
- duration** → How long it takes
- timing-function** → How it changes over time
- delay** → When it starts



Key Points :

- Transitions make changes smooth instead of instant.
- Control property, duration, timing function and delay.
- Tailwind provides simple and powerful transition utilities.
- Use transitions to create a better user experience.



Key Takeaway :

- Tailwind CSS transitions help you add **smooth and natural animations** to your UI with minimal effort and maximum impact.



7.14 Dark Mode

7.14.1 What is Dark Mode?

- * Dark mode is a color scheme that uses **dark backgrounds** and **light text**.
- * Tailwind CSS provides a **dark:** variant to apply utilities in dark mode.
- * It improves **readability** in low light and gives a **modern look** to your UI.

Example



7.14.2 Dark Mode Utility Classes

Category	Classes (with dark:)	Description	Example Class	Preview (Light → Dark)
Background Color	<code>dark:bg-gray-800</code> <code>dark:bg-black</code> <code>dark:bg-slate-900</code> <code>dark:bg-zinc-900</code>	Changes background color in dark mode.	<code><div class="bg-white dark:bg-gray-800 p-4 rounded"></code> Content <code></div></code>	Light Mode: Content → Dark Mode: Content
Text Color	<code>dark:text-white</code> <code>dark:text-gray-300</code> <code>dark:text-gray-400</code>	Changes text color in dark mode.	<code><p class="text-gray-800 dark:text-white"></code> This is a paragraph. <code></p></code>	Light Mode: This is a paragraph. → Dark Mode: This is a paragraph.
Border Color	<code>dark:border-gray-700</code> <code>dark:border-gray-600</code>	Changes border color in dark mode.	<code><div class="border border-gray-300 dark:border-gray-700 p-4 rounded"></code> Box <code></div></code>	Box → Box
Fill / Icon Color	<code>dark:fill-white</code> <code>dark:text-white</code>	Changes SVG / icon color in dark mode.	<code><svg class="w-6 h-6 text-gray-700 dark:text-white" ...></code> ...	☀️ → 🌙
Ring / Outline Color	<code>dark:ring-gray-600</code> <code>dark:outline-gray-600</code>	Changes focus ring or outline color.	<code><input class="border p-2 rounded focus:ring-2 focus:ring-blue-500 dark:focus:ring-gray-600" /></code>	→
Hover Effects	<code>dark: hover:bg-gray-700</code> <code>dark: hover:text-white</code>	Applies hover styles in dark mode also.	<code><button class="px-4 py-2 bg-blue-500 text-white rounded hover:bg-blue-600 dark: hover:bg-blue-400"></code> Hover Me <code></button></code>	Hover Me → Hover Me
Misc Utilities	<code>dark:opacity-80</code> <code>dark:shadow-dark</code>	Controls opacity, shadows and more.	<code><div class="shadow-md dark:shadow-dark dark:opacity-80 p-4 rounded"></code> Content <code></div></code>	Content → Content

7.14.3 How to Enable Dark Mode

1. Configure in tailwind.config.js

```
/** @type {import('tailwindcss').Config} */
module.exports = {
  darkMode: 'class', // or 'media'
  content: [
    './index.html',
    './src/**/*. {js,ts,jsx,tsx}"
  ],
  theme: {
    extend: {},
  },
  plugins: [],
}
```

darkMode: 'class' →
Use the 'dark' class on
<html> or <body> to
toggle dark mode.

Example:

```
<html class="dark">
  <body>
    ...
  </body>
</html>
```

darkMode: 'media' →
Follows the system
preference automatically.



7.14.4 Examples

```
<div class="bg-white dark:bg-gray-900 text-gray-800 dark:text-white p-4 rounded shadow">
  Card Content
</div>
```

```
<h1 class="text-gray-900 dark:text-white text-2xl font-bold">
  Welcome to Tailwind CSS
</h1>
```

```
<button class="px-4 py-2 bg-blue-600 text-white rounded hover:bg-blue-700 dark:bg-blue-500 dark: hover:bg-blue-400">
  Get Started
</button>
```

```
<input type="text" class="p-2 border border-gray-300 rounded dark:bg-gray-800 dark:border-gray-700 dark:text-white placeholder="Enter name" />
```

```
<svg class="w-6 h-6 text-gray-700 dark:text-white fill="none" stroke="currentColor" viewBox="0 0 24 24" ...>
  ...
</svg>
```

Light

Card Content

Welcome to Tailwind CSS

Get Started

Enter name

Dark

Card Content

Welcome to Tailwind CSS

Get Started

Enter name



7.14.5 Notes

- * Use **'dark:'** before any utility class to apply it only in dark mode.
- * Combine light and dark classes for beautiful themes.
- * Use **'class'** strategy for manual toggle with a button.
- * Use **'media'** strategy to follow the system (preferred color scheme).

Quick Tip

Dark mode enhances user comfort at night and reduces eye strain!

Key Points :

- ✓ Tailwind's **dark:** variant helps you create dark mode easily.
- ✓ Works with colors, borders, text, shadows, hover, focus and more.
- ✓ Configure darkMode in tailwind.config.js.
- ✓ Use **'class'** for manual toggle and **'media'** for system preference.

Key Takeaway :

Tailwind CSS dark mode utilities make it simple to build **beautiful, responsive** and **user-friendly** themes with minimal effort.



7.15 Reusable UI Components

7.15.1 What are Reusable UI Components?


- * Reusable UI components are building blocks that can be used multiple times across a project.
- * They save time, maintain **consistency** and improve code **maintainability**.
- * Tailwind CSS makes it easy to create beautiful and reusable components using utility classes.

Example

Same Button Component
Used in Different Places



Write once, use everywhere!



7.15.2 Common Reusable Components with Tailwind

Component	Description	Example (Preview)	Tailwind Classes (Example)	Use Cases
Button	Clickable button with styles.		<code><button class="bg-blue-600 text-white px-4 py-2 rounded-md hover:bg-blue-700 transition">Click Me</button></code>	Forms, actions, links, dialogs
Card	Container for content.		<code><div class="bg-white p-4 rounded-lg shadow-md border"> <h3 class="text-lg font-semibold"> Card Title</h3> <p class="text-gray-600">This is a card content.</p> </div></code>	Dashboards, product items, articles
Input Field	Text input for user data.		<code><input type="text" placeholder="Enter your name" class="w-full px-3 py-2 border rounded-md focus:outline-none focus:ring-2 focus:ring-blue-500"/></code>	Forms, search, authentication
Alert	Display important messages.		<code><div class="bg-green-100 text-green-800 border-l-4 border-green-500 p-4 rounded"> Success! Your data is saved. </div></code>	Success, error, warning, info messages
Badge	Small label or status indicator.		<code>New</code>	Status, labels, notifications
Navbar	Top navigation bar.		<code><nav class="flex justify-between items-center px-6 py-3 bg-white shadow"> ... </nav></code>	Website menus, navigation
Modal	Popup dialog window.		<code><div class="fixed inset-0 bg-black/50 flex items-center justify-center"> <div class="bg-white p-6 rounded-lg shadow-lg"> Modal content </div> </div></code>	Confirmations, forms, alerts
Footer	Bottom section of the page.		<code><footer class="bg-gray-900 text-white text-center py-4"> © 2025 MyWebsite </footer></code>	Copyrights, links, info

7.15.3 Component Example - Button Variants

Primary Button	<code><button class="bg-blue-600 text-white px-4 py-2 rounded-md hover:bg-blue-700 transition"> Primary</button></code>	
Secondary Button	<code><button class="bg-green-600 text-white px-4 py-2 rounded-md hover:bg-green-700 transition"> Secondary</button></code>	
Outline Button	<code><button class="border border-blue-600 text-blue-600 px-4 py-2 rounded-md hover:bg-blue-50 transition">Outline</button></code>	
Danger Button	<code><button class="bg-red-600 text-white px-4 py-2 rounded-md hover:bg-red-700 transition"> Delete</button></code>	

Key Points :

- ✓ Reusable components save time and ensure consistency.
- ✓ Tailwind utility classes help build clean and responsive components.
- ✓ Common components: Buttons, Cards, Inputs, Alerts, Badges, Navbar, Modals, Footers.
- ✓ Reuse, refactor and keep improving your component library.

Key Takeaway :



Tailwind CSS empowers you to build reusable UI components that are consistent, maintainable and scalable → the key to professional web development.

7.15.4 Component Composition Example

Product Title In Stock

This is a short description of the product.

₹499

Add to Cart View Details

7.15.5 Tips for Building Reusable Components

- * Use meaningful class names and consistent spacing.
- * Keep components simple and focused on one purpose.
- * Use **@apply** in your CSS file for repeated styles.
- * Organize components in separate files or partials.
- * Test components in different screen sizes.



Quick Tip

Build a library of components and reuse them across all your projects.



7.16 Professional Dashboard Design

7.16.1 What is a Professional Dashboard?


- * A dashboard is a visual interface that summarizes important data and metrics.
- * It helps users monitor performance, track progress and make **data-driven decisions**.
- * Professional dashboards are **clear, interactive, responsive** and **user-friendly**.
- * Good design improves usability and delivers insights at a glance.

Good Dashboard Principles

- 🎯 Focus on key metrics
- 👁️ Simple and clean layout
- 🎨 Consistent colors & typography
- 🖱️ Interactive & responsive
- 🕒 Real-time or up-to-date data
- 🛡️ Role-based access (if required)



7.16.2 Key Elements of a Professional Dashboard



7.16.3 Dashboard Best Practices

- ✓ Show only key metrics that matter.
- ✓ Use charts and graphs for quick understanding.
- ✓ Keep the layout simple and consistent.
- ✓ Use proper spacing, colors and typography.
- ✓ Provide date range filters and search.
- ✓ Ensure responsive design for all devices.
- ✓ Highlight important changes using colors.
- ✓ Add tooltips and labels for more clarity.
- ✓ Test with real users and improve continuously.



Key Takeaway :



Professional dashboard design turns complex data into meaningful insights and helps organizations make smarter and faster decisions.

7.16.4 Tools & Technologies

Category	Examples
Frontend	HTML, CSS, JavaScript, Tailwind CSS, React, Vue.js
Charts	Chart.js, ApexCharts, Recharts, D3.js
Backend	Node.js, Python (Django/Flask), PHP, Java (Spring Boot)
Database	MySQL, PostgreSQL, MongoDB
Others	Bootstrap, Ant Design, Google Data Studio, Power BI

7.16.5 Notes

- * A good dashboard tells the **story** of your data.
- * Design for **users**, not for looks only.
- * Always aim for **clarity, speed** and usability.
- * Keep improving based on user feedback and data insights.

Quick Tip

Great dashboards don't just show data, they help users take action!

